

TiCell P/60 FS

SODIUM CARBOXYMETHYL-CELLULOSE

CMC Technical Grade granulated form as additive for water based dispersion paints, excellent thickener with good adhesion ability; it helps film formation and increases viscosity, improves the covering power of paints and reduces paint run. Its abilities are the best when completely dissolved.

Average specification	TiCell P/60 FS
Bulk Density (g/l)	250-450
CMC content (dry basis %)	Min. 65
Degree of Substitution	0,55-0,65
Moisture content (%)	Max. 8
pH Value	7-11
Viscosity Brookfield (2% sol.) RVT 2/50 rpm	200-260 mPas

Packaging: 20 kg paper sacks, 720 kg palletized

Shelf life: 12 months

Origin: EU

Exlusive distributor:

Ti KEM Hungary LTD.
info@tikemhungary.hu

Note:

The data in this technical data sheet is provided for information only. It is correct to the best of our knowledge, information and belief at the date of its publication. All information comes from the producer. It does not constitute a specification and no liability is assumed, nor freedom from any existing patents.

TIKEM HUNGARY KFT.

Address: H-2536 Nyergesújfalu, Vadkörtefa u 1/B. 2/1.

Phone: +3670 428 0556

Email: info@tikemhungary.hu /office@tikemhungary.hu

Web: www.tikemhungary.hu