











SODIUM CARBOXYMETHYLCELLULOSE DTK HV 350 G

General specification:

 Appearance:	Yellowish granulated
 Application:	Adhesive, wall-paper glue
 Density:	400-650 g/l
 Active content:	min. 56 %
 Degree of substitution (DS):	0,75-0,8
 Moisture content (as packaging):	max. 12%
 pH:	8-11
 Viscosity (Brookfield 2% RVT2/50):	500-1000 mPas
 Storage temperature:	5-35 °C
 Warranty time:	min. 12 months

<u>Packaging:</u>	25 kg paper sacks on 1000 kg by pallet
<u>Shelf-life:</u>	Min. 12 months from the date of production Minimum order quantity is 1000 kg.
<u>Storage:</u>	Keep away from wet, vapour and direct sunlight! Keep it in the original packaging!
<u>Origin:</u>	EU
<u>REACH:</u>	Label free, non toxic material.

Exclusive distributor:

Ti KEM Hungary Kft.
info@tikemhungary.hu

* Note:

The data in this technical data sheet is provided for information only. It is correct to the best of our knowledge, information and belief at the date of its publication. All information comes from the producer. It does not constitute a specification and no liability is assumed, nor freedom from any existing patents. Please also read the material Safety Data Sheet before use.

TiKEM HUNGARY KFT.

Address: H-2536 Nyergesújfalu, Vadkörtefa u 1/B. 2/1.

Phone: +3670 428 0556

Email: info@tikemhungary.hu / office@tikemhungary.hu

Web: www.tikemhungary.hu